Bilanx bathing collection strike the balance <u>Design</u> <u>Safety</u>

Making life easier with style and confidence.

BILANX INSTALLATION INSTRUCTIONS

(for hollow wall and wood stud walls)

- 1. Remove Contents from box
- 2. Place Bilanx Grab Bar on the wall in your desired location
- 3. Mark the 2 elongated holes on each flange base
- 4. Remove Bilanx Grab Bar and drill ½" holes
- 5. Insert the 4 togglers (included) into the four holes
- 6. Slide the plastic collar against the wall
- 7. Snap of the excess plastic tabs
- 8. Remove the 2 flange bases from the Grab Bar by loosening the 3 set screws in each flange post

- Place the flange bases on the wall aligning the elongated holes in the flange base with the inserted togglers
- 10. Attach flange bases using the 4 machine screws provided, tighten and secure
- Slide the concealed flange covers over the Bilanx Grab Bar posts
- 12. Then slide the Bilanx Grab Bar posts over the flange base previously attached to the wall
- 13. Tighten all set screws
- 14. For applications where in–wall wood backing or wall studs are present please use the stainless steel wood screws provided in place of the togglers

** for the Soap Basket Grab Bar, Shampoo Shelf Grab Bar and the Corner Shelf Grab Bar please exclude steps 8, 10, 12 and 13 and simply attach using the stainless steel screws or toggle kit included.





Find Online: https://www.ezable.com/brands/Bilanx.html