

SPECIFICATIONS

Grab Bar, Stainless Steel, Straight
Part no.
GB (LENGTH) (QSS/HSS) (FINISH)

DESCRIPTION

TUBING MATERIAL

- Type 304 (18-8) stainless steel

DIMENSION "T"

- 1-1/4" O.D. x .049" (18 ga.) wall thickness (QSS)
- 1-1/2" O.D. x .049" (18 ga.) wall thickness (HSS)

FLANGE STYLE

- Mounting flanges are constructed of Type 304 (18-8) stainless steel, heliarc welded to the bar to form a single structural unit.
- Concealed, 14 ga. x 3" dia.

FINISH

- Standard - satin stainless
- Optional Powder coating (P.C.) in various colors
- Epoxy type DuPont #ELW-505-S9
- Adhesion per ASTM D3359 Method B
- Accelerated aging per ASTM G26 Method A
- Gloss per ASTM D 523
- Flexibility per ASTM D 522 Method A

MEETS

- ADA Guidelines section 4.26
- ASTM F 466-85 (re-approved 1990): Standard Consumer Safety
- Specification for Grab Bars and Accessories installed in the Bathing Area
- Federal Specification WW-P 541-8b, Amendment 1 4-16-1990
- ANSI 117.1 1998: Buildings and Facilities providing Accessibility and Usability
- F.H.A., V.A. and HUD requirements
- Commonwealth of Massachusetts Architectural Access Board
- California Building Code
- City of Los Angeles

INSTALLATION

- Factory Installed with #10x1-1/4" stainless self tapping screws in integral plywood backing.

